

Chubb Fire FX Range - FX Spray Foam

Fire Systems

Prevent Fire | Detect Fire | **Contain Fire** | Escape Fire

Product(s): FX Spray Foam



Model	FO6	FO9	CFO6	CF09
Product No.	7282/00	7283/00	7286/00	7287/00
Height (mm)	561	546	600	620
Width (mm)	300	365	310	290
Shell Diameter (mm)	150	190	150	190
Capacity (litres)	6L	9L	6L	9L
Test Pressure (bar)	33	33	33	33
Working Pressure at 20 C	15	15	15	15
Weight Full (kg)	9.5	13.8	10.6	15.7
Weight Empty (kg)	3.45	4.8	4.6	6.6
Discharge time at 20 C (secs)	30-40	50-60	30-40	40-50
Minimum Effective Discharge (%)	90	90	90	90
Temperature Range (C) water only	+5 to +60°C	+5 to +60°C	+5 to +60°C	+5 to +60°C
Temperature Range (C) with LFA	-10 to +60°C	-10 to +60°C	-10 to +60°C	-10 to +60°C
Fire Rating without LFA	21A : 183B	27A : 233B	21A : 183B	27A : 233B
Fire Rating with LFA	13A : 113B	13A : 183B	13A : 113B	13A : 183B