

POWDER



- Features:**
- 15 bar working pressure gives greater application reach ensuring user safety.
 - Simple seize and squeeze method of operation combined with controllable discharge for maximum fire-fighting performance and minimum mess.
 - Non-damaging plastic skirt.*
 - Colour coded area to establish at-a-glance contents recognition.
 - Unique tamper evident safety pin with OK indicator to reduce accidental discharge.
 - Chubb powder extinguishers are compatible with Chubb Fire's range of spray foam extinguishers.

*Excludes EP1, EP2

POWDER

PRODUCT SPECIFICATION

MODEL PRODUCT NO.	EP1 7301/00	EP2 7303/00	EP3 7305/00	EP6 7307/00	EP9 7309/00
Height - Approx (mm)	320 <small>inc. bracket</small>	376 <small>inc. bracket</small>	450	566	605
Width - Approx (mm)	130 <small>inc. bracket</small>	135 <small>inc. bracket</small>	290	280	290
Shell Diameter (mm)	87	112	130	160	190
Capacity (kg)	1	2	3	6	9
Test Pressure (bar)	25	25	25	25	25
Working Pressure at 20°C	15	15	15	15	15
Weight Full - Approx (kg)	2.1 <small>ex. bracket</small>	3.55 <small>ex. bracket</small>	5.8	9.9	14.1
Weight Empty - Approx (kg)	1.1 <small>ex. brack</small>	1.5 <small>ex. brack</small>	2.8	3.8	5
Discharge time - Approx	8 secs	14 secs	13 secs	16 secs	21 secs
Minimum Effective Discharge (%)	90	90	90	90	90
Temperature Range	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C
Fire Rating	8A:34B	13A:70B	21A:89B	34A:233B	43A:233B

Dry powder is a highly versatile Class A, B & C fire-fighting medium for any fire risk. In addition to dealing with electrical hazards, flammable liquids and gases, powder is also effective for vehicle fires. Fire ratings provide a means of measuring the effectiveness of an extinguisher in terms of the maximum size of fire that can be extinguished. Class A rating is related to a wooden crib fire 0.5m wide x 0.56m high x length. The rating figure is ten times the length in metres, eg. 13A uses a crib 1.3 metres long. Class B is related to fire surface area and the rating figure to the quantity of flammable liquid in a ratio of 1/3 water, 2/3 fuel that can be extinguished in a circular tray.

